



WWW.MAYTAGCOMMERCIALLAUNDRY.COM



# MAYTAG

Commercial Laundry

COIN LAUNDRY STORE



1-800-688-0208

Maytag, 403 W. Fourth St. N., Newton, IA 50208

CL654 PRINTED IN THE U.S.A. 02/02



A close-up, slightly blurred photograph of a person's hand with brown nail polish inserting a silver coin into a coin slot on a white laundry machine. The machine has a control panel with buttons and a small display. The background is out of focus, showing more of the machine and a hint of a blue object.

LAUNDRY SOLUTIONS FROM A  
PARTNER YOU CAN *DEPEND* ON.

No matter what your commercial laundry needs are, Maytag has a solution. We're dedicated to delivering the best quality, service, dependability and value to our customers — so you can offer the same to your customers day after day. We're not just your supplier; we're your partner. One who's committed to helping you build your business.

# COIN LAUNDRY STORE

## LOAD UP ON PROFITS.

When you're looking for the right equipment for a coin laundry store, it's not just about performance — it's about profit. And Maytag® commercial laundry equipment delivers both. In fact, we're dedicated to helping you build your bottom line with new ways to cut operating costs, increase efficiency and create greater customer satisfaction.

Maytag® products are built to last with high-quality parts, easy-to-service designs and special coatings that resist scratches and stains to stay looking like new for years. But the value you get from Maytag doesn't end with our products.

We have a nationwide network of expert distributors who can help with everything from planning the right location and product mix to financing and installation — even retrofitting an existing laundry with Maytag® equipment. Plus, we stand behind our commercial laundry products with one of the best warranties in the business. So when your profitability depends on quality equipment and service, remember — you can depend on Maytag.



The **MAYTAG® COMMERCIAL NEPTUNE®** high-efficiency washer is **ENERGY STAR®**-rated — and it can cut your water, energy and sewer costs up to 50%\* or more compared to conventional top-load washers.



Maytag is the **#1-PREFERRED BRAND OF TOP-LOADING WASHERS** by coin laundry owners/managers across America. Plus, Maytag® top-loading commercial washers **LAST LONGER** than other leading brands of top-loading commercial washers.

The new **MAYTAG® DEPENDABLE CARE®** stack dryer is one of the fastest-drying, most energy-efficient stack dryers on the market. It features an exclusive dual **THERMOGUARD™** system that protects clothes against damaging overheating.



Maytag's advanced **COMPUTER TRAC®** controls give you flexibility to set vend prices by day, time and washing/drying options. They also give your customers **MAXIMUM CONVENIENCE** with a coin countdown and time remaining display.

Maytag is the most recognized and **MOST PREFERRED NAME** in the laundry industry. Having "Maytag-Equipped" on your outdoor sign gives you **INSTANT CREDIBILITY** — without paying any franchising fees.



\* Based on testing with an 8-pound AHAM load with 15% hot-, 55% warm- and 30% cold-water wash at five turns per day and 365 days per year. Water, gas and sewer costs based on 2000 average U.S. national rates. Individual savings may vary.





Our Fastest-Selling Washer

**MAYTAG® COMMERCIAL NEPTUNE® HIGH-EFFICIENCY WASHERS**

- Save up to 50% or more a year on water, energy and sewer costs compared to conventional top-load washers.\*
- High-speed extraction saves drying time and energy.
- No agitator means 32% greater capacity for big, bulky loads.
- Design meets ADA accessibility guidelines.



**MAYTAG® COMMERCIAL TOP-LOAD WASHERS**

- Our commercial top-load washers last longer than other leading brands.
- Tub opening is one of the largest in the industry for easy loading and unloading.
- Dependable Drive® transmission has fewer parts for fewer repairs.
- Zinc-coated steel cabinet and porcelain-enamel top stay looking like new for years.



**MAYTAG® COMMERCIAL RIGID-MOUNT FRONT-LOAD WASHERS**

- Built like battleships, our multi-load washers are among the heaviest on the market.
- Heavy-duty bearings are lubricated and sealed for longer life and smoother operation.
- All-304 stainless steel top, front and sides mean each unit looks as great as it performs.



**MAYTAG® COMMERCIAL SINGLE-LOAD STACK DRYER/DRYERS**

- Airflow system delivers fast, powerful, efficient drying performance.
- Extra-large doors and drums allow easy loading and unloading.
- Two drying pockets fit in the floor space of one.
- Tri-Coat™ cabinet protection keeps cabinet looking like new.



**MAYTAG® COMMERCIAL NEPTUNE® STACK WASHER/DRYERS**

- A full-size Neptune® washer and a full-size, super-capacity dryer fit in the floor space of a washer alone.
- Washer saves up to 50% on water, energy and sewer bills compared to top-load washers.\*
- Efficient drying saves time — dry clothes in the time it takes to wash them.



**MAYTAG® COMMERCIAL MULTI-LOAD DRYERS**

- Energy-efficient airflow system dries big loads fast.
- Large waist-high door allows easy loading and unloading.
- Heavy-duty belt drive system delivers trouble-free performance.



**MAYTAG® DEPENDABLE CARE® MULTI-LOAD STACK DRYER/DRYERS**

- Two drying pockets fit in the floor space of one conventional multi-load dryer.
- This is one of the fastest, most energy-efficient stack dryers on the market.
- Exclusive dual ThermoGuard™ system protects laundry against damaging overheating.

\* Based on testing with an 8-pound AHAM load with 15% hot-, 55% warm- and 30% cold-water wash at five turns per day and 365 days per year. Water, gas and sewer costs based on 2000 average U.S. national rates. Individual savings may vary.

CHOOSE FROM THREE PAY OPTIONS.



Coin-Drop



Coin-Slide



Debit Card-Ready

To prevent slugging, coin-drop models feature an optical sensor that measures the size, weight and drop speed of a coin before it's accepted. Coin-slide models are equipped to accept a variety of slides. And our state-of-the-art debit card-ready models make “change” a thing of the past.

Maytag® Commercial Laundry Specifications — WASHERS

	Neptune® Washer	Top-Load Washer	Multi-Load Washers				
WASHER SPECIFICATIONS							
MODELS	MAH21	MAT12	MFR18	MFR25	MFR35	MFR50	MFR80
MOTOR							
Variable-speed, reversing, high-efficiency, switched reluctance	•						
Reversing, thermoprotected		•					
2-speed			•	•	•	•	•
HP in wash (kw)	.25 (.19)	.5 (.37)	.19 (0.1)	.18 (.13)	.45 (.34)	.5 (.37)	1 (.75)
HP in spin or extract (kw)	.5 (.37)	.5 (.37)	.75 (.55)	1 (.75)	2 (1.5)	2.5 (2.0)	5 (3.7)
Volts (Hz)	120 (50/60)	120 (60)					
Export models — volts (Hz)	240 (50) 100 (50/60)	240 (50)					
Voltage/breaker size: 120 volts/1 PH — amp 208 – 240 volts/1 PH (3-wire + ground) — amp 208 – 240 volts/3 PH (3-wire + ground) — amp	15	15	20 15	20 15	20 15	20 15	30
SPEED							
Wash speed — maximum rpm <i>Stack</i>	47 – 51 47 – 51		48	48 – 52	45	45	41
Extract speed — maximum rpm <i>Stack</i>	1,000 800	618	550	550	450	450	510
Extract speed — maximum g-force <i>Stack</i>	307 200	110	90	90	80	80	130
APPROXIMATE WATER USAGE							
Hot-water usage, average per cycle — gal. (liters) <i>Stack</i>	2.25 (8.5) 2.25 (8.5)	6.5 (24.6)			varies by cycle		
Overall — gal. (liters)  <i>Stack</i>	13 – 16 (49 – 60.1)*  18 – 21 (68.1 – 79.5)*	31.5 (119.2)** 29 (109.8) w/adj. setting			varies by cycle		
WATER INLET/HOSE							
Water inlet — in. (cm)			3/4 (1.9)	3/4 (1.9)	3/4 (1.9)	3/4 (1.9)	3/4 (1.9)
Operating pressure — psi (bar)	15 – 120 (1 – 8)	15 – 120 (1 – 8)	30 – 85 (2 – 6)	30 – 85 (2 – 6)	30 – 85 (2 – 6)	30 – 85 (2 – 6)	30 – 85 (2 – 6)
Inlet hose length — ft. (m)	4 (1.22)	4 (1.22)					
Drain hose, inside diameter x length — in. (cm)	1 x 42 (2.54 x 106.7)	1 x 42 (2.54 x 106.7)	2.5 x 30 (6.5 x 76.2)	2.5 x 30 (6.5 x 76.2)	2.5 x 30 (6.5 x 76.2)	2.5 x 30 (6.5 x 76.2)	2.5 x 30 (6.5 x 76.2)
CAPACITY							
Lbs. (kg)			18 (8.2)	25 (11.3)	35 (15.9)	50 (22.7)	80 (36.3)
Cylinder volume — cu. ft. (liters)	2.9 (82.1)	2.5 (70.8)	2.61 (73.9)	3.27 (92.6)	5.72 (162)	7.68 (217)	11.79 (333.8)
Cylinder diameter — in. (cm)	21 1/2 (54.6)	20 1/2 (52.1)	21 (53.3)	21 (53.3)	27 9/16 (70)	27 9/16 (70)	36 (91.4)
Cylinder depth — in. (cm)	16 (40.6)	13 (33)	13 (33)	16 1/2 (41.9)	16 9/16 (42)	22 3/4 (57.8)	20 (50.8)
COLORS							
White	•	•					
Bisque (select models)	•	•					
Stainless Steel			•	•	•	•	•
APPROXIMATE WEIGHT							
Crated — lbs. (kg)	225 (102)	224 (102)	342 (155)	408 (185)	686 (311)	877 (398)	1,788 (811)
Uncrated — lbs. (kg)	195 (88)	198 (90)	320 (145)	373 (169)	629 (285)	783 (355)	1,519 (689)
DIMENSIONS							
Height — in. (cm)	44 1/8 <sup>†</sup> (112)	44 1/8 <sup>†</sup> (112)	41 3/8 (105.1)	44 7/8 (114)	51 3/4 (131.5)	51 3/4 (131.5)	57 (144.8)
Width — in. (cm)	27 (68.6)	25 1/2 (64.8)	26 (66)	26 (66)	33 11/16 (85.5)	33 11/16 (85.5)	43 1/2 (110.5)
Depth — in. (cm)	28 1/4 <sup>††</sup> (71.8)	26 3/4 (67.9)	24 5/8 (62.5)	30 3/4 (78)	31 11/16 (80.5)	40 3/4 (103.5)	40 3/4 (103.5)
Door opening — in. (cm)	15 1/2 (39.4)	16 (40.6)	11 1/8 (28.3)	11 1/8 (28.3)	14 1/2 (36.8)	14 1/2 (36.8)	20 5/32 (51.2)

For detailed specifications and dimensional illustrations, please visit our Web site, [www.maytagcommerciallaundry.com](http://www.maytagcommerciallaundry.com).

\* Average based on testing with an 8-pound AHAM load. If optional additional rinse is used, add 5 gallons; not dependent on pressure or time.

\*\* Average based on testing with a 14-pound AHAM load.

<sup>†</sup> Dimensions will vary according to adjustment of leveling legs; add 2" min.

<sup>††</sup> Includes hinge on back of washer.

Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

Maytag® Commercial Laundry Specifications — DRYERS AND STACKED UNITS

	Multi-Load Dryers		Multi-Load Stack Dryer/ Dryer	Single-Load Stack Dryer/ Dryer	Neptune® Stack Washer/ Dryer
DRYER AND STACKED UNIT SPECIFICATIONS					
MODELS	MDG30	MDG50	MLG32	MLE/G23	MLE/G19
MOTOR					
HP (kw)	.5 (.373)	.75 (.560)	.5 (.373)	.25 (.19)	.25 (.19)
Single-phase, thermoprotected against overload, auto-reset	.	.	.	.	.
ELECTRICAL REQUIREMENTS					
Volts (Hz)					
Electric models				240 (60)	240 (60)
Gas models	110 (60)	110 (60)	110 (60)	120 (60)	120 (60)
Export models — volts (Hz)				240 (50)	240 (50)
Breaker/fuse requirement — amp				30	30
Electric models (each drying chamber)				60	
Electric models — export (one terminal block per stack)				15	
Gas models (each drying chamber)	20	20	20		15
Approx. overall wattage draw per drying chamber				5,900	5,900 (6,300 incl. washer)
Export models — wattage draw per drying chamber				4,900	4,900
CAPACITY					
Lbs. (kg)	30 (13.6)	50 (22.7)	30 (13.6)		
Cu. ft. (cu. m)	12.3 (.348)	18.3 (.518)	10.3 (.292)	6.0 (0.17)	6.0 (0.17)
Tumbler diameter — in. (cm)	30 (76.2)	32 3⁄4 (83.2)	27 1⁄4 (69.2)		
Tumbler depth — in. (cm)	30 (76.2)	37 1⁄2 (95.3)	30 (76.2)		
AIRFLOW					
Domestic — cu. ft. per minute (cu. m) per pocket	600 (17)	600 (17)	420 (11.9)	220 (6.2)	220 (6.2)
Export models — cu. ft. per minute (cu. m) per pocket				180 (5.0)	180 (5.0)
EXHAUST					
Exhaust duct diameter — in. (cm) SEE NOTES.	8 (20.3)/ 10 (25.4)*	8 (20.3)/ 10 (25.4)*	8 (20.3)	2 inlets 4 (10.2)**	4 (10.2)**
GAS RATING (MLG MODELS)					
Per drying chamber — BTU/hr. (kcal/hr.)	90,000 (22,680)	130,000 (32,760)	80,000 (20,160)	24,000 (6,048)	24,000 (6,048)
Gas inlet — in. (cm)	1⁄2 (1.3)	1⁄2 (1.3)	3⁄4 (1.9)	2 inlets 1⁄2 (1.3)	1⁄2 (1.3)
COLORS					
White	.	.	.	.	.
Bisque (select models)			.	.	
APPROXIMATE WEIGHT					
Crated — lbs. (kg)	550 (250)	625 (284)	915 (415)	282 (128)	335 (152)
Uncrated — lbs. (kg)	500 (227)	565 (256)	875 (397)	255 (116)	303 (137)
DIMENSIONS					
Height — in. (cm)	72 (182.9)	72 (182.9)	78 1⁄4 (198.8)	71 1⁄2 (181.6) <sup>††</sup>	71 1⁄2 (181.6) <sup>††</sup>
Width — in. (cm)	31 3⁄8 (79.7)	34 1⁄4 (87)	29 7⁄8 (75.9)	27 (68.58)	27 3⁄16 (69.1)
Depth — in. (cm)	43 (109.2)	49 5⁄8 (126)	52 (132)	27 1⁄2 (69.9)	27 1⁄2 (69.9)*
Door opening diameter — in. (cm)	21 1⁄2 (54.6)	21 1⁄2 (54.6)	21 1⁄2 (54.6)	18 1⁄2 (47)	18 1⁄2 (47)
For detailed specifications and dimensional illustrations, please visit our Web site, <a href="http://www.maytagcommerciallaundry.com">www.maytagcommerciallaundry.com</a> .					
* Requires 8" (20.3 cm) material if venting horizontally; 10" (25.4 cm) if venting vertically. Dryer must be connected to 1⁄2" gas line.					
** Use a minimum of 4" (10.2 cm) diameter rigid aluminum or galvanized steel duct. Never use plastic, non-metal or combustible duct.					
<sup>†</sup> See MAH21 for washer specifications.					
<sup>††</sup> Dimensions will vary according to adjustment of leveling legs; add 2" min.					
▲ Additional depth with venting will take from 1 1⁄8" to 7" (2.9 cm to 17.9 cm) of depth depending on the vent method used.					
Because of continuous product improvement, Maytag reserves the right to change specifications without notice.					

MAYTAG® LIMITED WARRANTY.

At Maytag, we believe durable goods should remain just that. That's why every Maytag® appliance is constructed of the highest-quality materials and with the utmost in precision craftsmanship. It's also why we back every Maytag® appliance with a strong warranty. See your Maytag distributor for details.



Maytag® Commercial Neptune® High-Efficiency Washers And Maytag® Commercial Neptune® Stack Washer/Dryers

- 2 Years All parts
- 5 Years Washer motor, wash basket, shaft assembly, bearings, seals and external cabinet against rust-through, including the shell, top, door and frame

Maytag® Commercial Top-Load Washers

- 2 Years All parts
- 5 Years Washer transmission and external cabinet against rust-through, including the top, lid and baseframe

Maytag® Commercial Multi-Load Washers

- 2 Years All parts
- 5 Years Shell, welded frame assembly, basket, shaft assembly, bearings and seals

Maytag® Commercial Single-Load Stack Dryer/Dryers

- 2 Years All parts
- 5 Years External cabinet against rust-through, including the top, baseframe and dryer door

Maytag® Commercial Multi-Load Dryers And Maytag Dependable Care® Commercial Multi-Load Stack Dryer/Dryers

- 2 Years All parts

<sup>†</sup> Ask a sales associate for details.  
For a period from the date of original purchase through the times listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.