

Leading the way in laundry.

How do you do laundry? Is it a daily ritual or a once-a-week chore? After decades of solving the most common laundry problems, we're certain we have the laundry pair to make short work of your laundry day — from heavy-duty machines loaded with time-saving features to high-efficiency models that save you money on energy and water.



WHICH MODEL IS RIGHT FOR YOUR LAUNDRY ROOM?

Answer these questions to help determine which models and features you need to solve your everyday challenges.

- 1. How many loads of laundry do you do each week?
- 2. Do you wash extra-dirty items two or three times to make sure they really get clean?
- 3. Do you flat-dry or hang-dry special items to make sure they won't shrink?
- 4. Would you prefer the versatility of a washer/dryer pair that can be configured side-by-side or as a stack?
- 5. How often do you hand-wash delicate items?
- 6. Do you know the secret to treating different types of stains?

5

Maytag® Compact Front-Load Laundry

Compact In Size — Not Capacity.

STANDARD FEATURES YOU DEPEND ON FROM MAYTAG

WASHER FEATURES

- TurboClean Wash System
- Large Capacity (2.4 Cu. Ft.)
- Easy-To-Use Electronic Touch-Pad Controls
- 22 Cycles
- Wrinkle Control, Delicates, Hand Washables And Quick Cycles
- Extra Rinse, Rinse Only And Rinse & Spin Options
- 1,200-rpm Spin Speed
- 5 Water Temperature Combinations
- Automatic Temperature Control
- IntelliFill™ Water Level Control

- Automatic Detergent, Bleach And Fabric Softener Dispenser
- Up To 19-Hour Delay Wash

DRYER FEATURES

- GentleBreeze[™] Drying System
- Large Capacity
- AutoDry Dryness Control
- Wrinkle Release And Air Fluff Cycles;
 Wrinkle Prevent And Cool Down
- Sensor Dry, Damp Dry And Time Dry Cycles

- Reversible Door
- Stacking Kit Available (MAL2424AXX)

BUILT-TO-LAST™ FEATURE

- Lifetime Stainless Steel Wash Basket
- Stainless Steel Dryer Drum





Color: White





Flexible Under-Counter Or Stacked Installation

Measuring just 231/2" wide, 24" deep and 331/4" high*, the new Maytag® compact frontload washer and dryer fit in tight spaces to take up even less of your precious floor space.

* With 7/8" adjustable leveling legs. Actual dryer depth: 23³/4". Control panel adds 2" to washer depth.



Compact In Size — Not Capacity

They save space on the outside, but inside, the compact front-load washer and dryer can easily handle your everyday-sized loads — they each hold up to 16 bath towels.



High Efficiency

High-efficiency wash system lowers utility bills by using less water and energy. Fast spin speeds reduce drying time and energy costs.



Powerful Cleaning Without An Agitator

TurboClean wash system gently tumbles clothes through a pool of detergent and water while waterfall baffles scoop water and shower it onto laundry for outstanding cleaning.













13

For additional feature information, see specification charts on pages 22 and 23.

Maytag[®] Atlantis[®] Laundry

Outstanding Cleaning You Can Depend On For Years.

STANDARD FEATURES YOU DEPEND ON FROM MAYTAG

WASHER FEATURES

- HydroClean[™] Wash Action
- Super Capacity (3.2 Cu. Ft.)
- Exclusive TurboRinse™ System
- Regular/Whites, Permanent Press, Delicates And Handwash Cycles
- Extra Rinse Option
- Automatic Fabric Softener Dispenser
- Bleach Dispenser
- Exclusive Easy-Access Sloped Front With Extra-Large Lid

DRYER FEATURES

- GentleBreeze[™] Drying System
- Oversize Capacity
- Adjustable Degree Of Dryness
- Permanent Press Cycle
- Wrinkle Release
- Time Dry, Air Fluff And Damp Dry Cycles
- Delicate Temperature Setting
- Exclusive Easy-Access Sloped Front With Extra-Large Reversible Door


BUILT-TO-LAST™ FEATURES

- Heavy-Duty Lifetime Tub[™] Warranty
- Premium Porcelain-Enamel Top And Lid
- DuraCushion™ Dryer Drum
- Heat-Resistant Air Seals




HydroClean™ Wash System With Exclusive TurboRinse™ System

Unique wash action features a specially designed agitator and three-way residue removal TurboRinse[™] system for outstanding cleaning.



Commercial-Quality Stainless Steel Tub

Resists corrosion, stains and harsh chemicals and offers a Lifetime Tub™ Warranty — no one has a stronger warranty. (select models)



Super Capacity

3.2 cu. ft. capacity allows you to wash more clothes in a single load — including bulky towels to save time.



MAV9750 WASHER

Standard Features Plus:

- 301 Premium-Grade Stainless Steel Washtub
- HydroFlex[™] Plus Agitator CorrecTemp[™] Control Option

STAINLESS

Standard Features Plus:

Stainless Steel Washtub

 HydroFlex[™] Plus Agitator CorrecTemp[™] Control

• 4 Temperature Combinations Prewash And Presoak Options

vary depending on utility rates, model replaced and usage.

• 301 Premium-Grade

• Infinite Water Levels

- Infinite Water Levels
- 7 Temperature Combinations
- Prewash And Presoak Options

SAVE \$70 PER YEAR*

MAV9504E WASHER

- · Soak Only, Quick Wash, Cottons/Colors And Sweaters Cycles
- Extended Spin Option
- Spot-Treat With Finger Faucet
- Ouiet Plus II Sound Package
- Colors: White, Bisque



Standard Features Plus:

- CorrecTemp[™] Control Option

MAV8551 WASHER

- Steel Washtub
- Infinite Water Levels

- HydroFlex[™] Plus Agitator
- 7 Temperature Combinations

MAV7551 WASHER

Standard Features Plus:

CorrecTemp[™] Control

• 5 Water Levels

• Prewash Option

* Compared to an average conventional washer. Based on D.O.E. test method with average conventional washer, 10 loads per week, average water and sewer rates and 2000 electrical energy rate. Savings will

HydroFlex[™] Plus Agitator

• 5 Temperature Combinations

- 301 Premium-Grade Stainless

- Prewash Option
 - Soak Only, Quick Wash And Cottons/Colors Cycles
 - Quiet Plus II Sound Package

· Soak Only, Quick Wash And

Cottons/Colors Cycles

Color: White, Bisque

• Quiet Plus Sound Package

Colors: White, Bisque



MAV7504E WASHER

Standard Features Plus:

- HydroFlex[™] Plus Agitator CorrecTemp[™] Control
- 5 Water Levels
- 4 Temperature Combinations
- Prewash And Presoak Options
- Soak Only, Quick Wash And Cottons/Colors Cycles
- Quiet Plus II Sound Package

Color: White



MAV6451 WASHER

Standard Features Plus:

- HydroFlex[™] Agitator
- 4 Water Levels
- 4 Temperature Combinations
- Quiet Pack Sound Package

Colors: White, Bisque

For additional feature information, see specification charts on pages 22 and 23.



MDE/G8400 DRYER

Standard Features Plus:

- IntelliDry® Dryness Control With Sensor
- Infinite Temperature Settings
- Extended Tumble
- Easy-Storage Drying Rack • Ultra Care Temperature Setting
- Quiet Plus Sound Package

Colors: White, Bisque

Drvel® Cvcle

Dryel® is a registered trademark of Procter & Gamble



MDE/G7400 DRYER

Standard Features Plus:

- IntelliDry® Dryness Control With Sensor
- Quiet Pack Sound Package

Colors: White, Bisque

• 4 Temperature Settings



MDE/G6400 DRYER

Standard Features Plus:

- Automatic Dryness Control 4 Temperature Settings
- Quiet Pack Sound Package
- Colors: White, Bisque

· Soak Only, Quick Wash,

• Spot-Treat With Finger Faucet

• Quiet Plus III Sound Package

Cottons/Colors And

Sweaters Cycles

Colors: White, Bisque

Maytag[®] Laundry

Outstanding Cleaning You Can Depend On For Years.

STANDARD FEATURES YOU DEPEND ON FROM MAYTAG

WASHER FEATURES

- DependableClean[™] Wash System
- Super Capacity (3.3 Cu. Ft.)
- Regular, Wrinkle-Free Fabrics And **Delicates Cycles**
- Extended Spin
- Bleach And Fabric Softener Dispensers
- Extra-Large Lid Opening
- SturdySpin[™] Suspension System

DRYER FEATURES

- GentleBreeze[™] Drying System
- Oversize Capacity Plus
- Time Dry, Wrinkle-Free Fabrics And Air Fluff Cycles
- Delicate Temperature Setting
- Extra-Large Reversible Door

BUILT-TO-LAST™ FEATURES

- Heavy-Duty Lifetime Tub[™] Warranty
- Powder-Coat Finish On Top And Lid
- DuraCushion[™] Dryer Drum



Built To Last For Years

Depend on commercial-quality parts and features to keep your Maytag® washer and dryer working for years.

† Ask for details.



DependableClean™ Wash System

Special agitator and four-part wash system washes away dirt and removes residue.



Super Capacity

3.3 cu. ft. capacity allows you to wash more clothes in a single load to save time.



SAV4655E WASHER

Standard Features Plus:

- FlexCare[™] Agitator
- Infinite Water Level Control
- 4 Temperature Combinations
- 25 Cycles
- Automatic Temperature Control
- Soak Only Cycles
- Extra Rinse Option
- 710-rpm Spin Speed
- Finger Faucet
- Quiet Plus Sound Package
- Handwash, Prewash And



SAV2655 WASHER

Colors: White, Bisque

Standard Features Plus:

- FlexCare[™] Agitator
- 4 Water Levels
- 4 Temperature Combinations
- 13 Cycles

- Handwash Cycle
- Extra Rinse Option
- Quiet Pack Sound Package

Color: White



SAV3655 WASHER

Standard Features Plus:

- FlexCare[™] Agitator
- 4 Water Levels
- 4 Temperature Combinations
- 4 Wash/Spin Speed Combinations
- 22 Cycles
- Handwash And Prewash Cycles
- Extra Rinse Option
- Quiet Pack Sound Package

Color: White



SAV2555 WASHER

Standard Features Plus:

- FlexCare[™] Agitator
- 4 Water Levels
- 4 Temperature Combinations
- 10 Cycles
- Quiet Pack Sound Package

Color: White



SDE/G4606 DRYER

Standard Features Plus:

- IntelliDry® Dryness Control
- Moisture Sensor
- Variable Temperature Settings
- Ultra Care Temperature Setting • 12 Cycles
- Damp Dry Cycle
- Wrinkle Release
- Extended Tumble Option
- Quiet Plus Sound Package

Color: White



SDE/G2606 DRYER

- Automatic Dryness Control

Color: White



SDE/G3606 DRYER

Standard Features Plus:

- Automatic Dryness Control
- 4 Temperature Settings
- 12 Cycles
- Damp Dry Cycle
- Wrinkle Release
- Extended Tumble Option
- Quiet Plus Sound Package

Colors: White, Bisque



Standard Features Plus:

- 3 Temperature Settings
- 7 Cycles

ALSO AVAILABLE LSE/G7806 MAYTAG® STACKED WASHER AND DRYER

A full-size washer and dryer pair in half the floor space.

Features:

- DependableClean[™] Wash System
- Bleach And Fabric Softener Dispensers
- GentleBreeze[™] Drying System

Colors: White, Bisque







For additional feature information, see specification charts on pages 22 and 23.

	Maytag [®] Compact												
	Front-Load Washer	Maytag® Atlantis® Washers								Maytag® Washers Stacked			
Models	I MAH2400	MAV9750	MAV9504E	MAV8551	MAV7551	MAV7504E	MAV6451	I SAV4655E	SAV3655	SAV2655	SAV2555	LSE/G7806	
FEATURES								5.11.0552	5555	U.1.2000	J	202/0/000	
ENERGY STAR®-Qualified	*		*			*		*					
Capacity — cu. ft.	2.4	3.2	3.2	3.2	3.2	3.2	3.2	3.3	3.3	3.3	3.3	2.5	
Controls	LED	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	
Washtub	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Polymer	Polymer	Polymer	Polymer	Polymer	Polymer	Polymer	Porcelain	
HydroFlex™ Agitator		Plus	Plus	Plus	Plus	Plus	•	,	,	,	,		
FlexCare™ Agitator													
Motor Speed	Universal	Two-Speed	Two-Speed	Two-Speed	Two-Speed	Two-Speed	Two-Speed	Two-Speed	Two-Speed	Two-Speed	Two-Speed	One-Speed	
Speed Combinations	4	6	6	5	5	5	4	4	4	3	3		
TurboClean Wash System													
HydroClean™ Wash System		•	-	•			-						
DependableClean™ Wash System									•			-	
TurboRinse™ System				•									
PureClean™ Rinse System								•		•			
Extended Spin		•						•		•			
Water Level Control	IntelliFill™	Infinite	Infinite	Infinite	5	5	4	Infinite	4	4	4	3	
Water Temp. Combinations	5	7	4	7	5	4	4	4	4	4	4	3	
Automatic Temp. Control/ CorrecTemp™ Control		-	-	-		-		-					
Warm Rinse Option		•		•				•		•			
Extra Rinse Option	-	•	•	•		•		•	•	•			
Delay Wash Option	19-Hour												
Delicates Cycle		•	-	•		-				•		-	
Handwash Cycle	•	•	-	•		-		-		•			
Presoak/Pretreat Cycle		-	•	•		-							
Prewash Cycle		•	•	•	•	-		•	•				
Soak Only Cycle		•	-	•	•	-		•					
Permanent Press/Wrinkle-Free Cycle	•	•	•	•	•	•		•	•	•		-	
Colors Cycle	-												
Cottons/Colors Cycle		•	-	-	•	-							
Sweaters Cycle		•	•										
Quiet Cycle Select	•	•	•	•	•	•	•	•	•	•	•		
Spot-Treat With Finger Faucet		•	•					•					
Bleach Dispenser	•	•	•	•	•	•	•	•	•	•	•	-	
Fabric Softener Dispenser	•	•	•	•	•	•	•	•	•	•	•		
Detergent Dispenser	el l							0 10"	0.1011				
End-Of-Cycle Signal	Chime	Remind						On/Off	On/Off				
Quick Setting/Quick Wash	•	•	•	•	-:-	•							
Easy Access	•	0.1.01.0	0.1.01.00	0.1.01.0		0.1.01.0	0.1+0.1	0.1.01	01.01	01.01	01.01	0.1.10.1	
Sound Package	Contain	Quiet Plus II	Quiet Plus III	Quiet Plus II	Quiet Plus	Quiet Plus II	Quiet Pack	Quiet Plus	Quiet Pack	Quiet Pack	Quiet Pack	Quiet Pack	
Self-Cleaning Lint Removal	System	System	System	System	System	System	System	Filter	Filter	Filter	Filter	Filter	
Six-Point Suspension System		•	•	•	•	•	-	_		_			
SturdySpin™ Suspension System			_			_		•		-	•		
Rear Self-Levelers		•	•	•	•	•	•	•	•	•	•	•	
Color Availability: White								•		•		-	
	_	-	•	-	-:-	•		-	•	-	•	⊢:	
Bisque			_	-	_								


MAYTAG® COMPACT FRONT-LOAD WASHER



MAYTAG® COMPACT FRONT-LOAD WASHER

HEIGHT -- IN. (CM): 33% (84.5) WIDTH -- IN. (CM): 23½ (59.7) **DEPTH** — IN. (CM): 24 (61) **DEPTH (WITH DOOR OPEN)** — IN. (CM): 41½ (104.3) MOTOR: 1/2 HP, 120-volt, 60 Hz.

MAYTAG® ATLANTIS® WASHERS




MAYTAG® ATLANTIS® WASHERS

MOTOR: 1/2 HP, 120-volt, 60 Hz, single-phase, thermally protected against overload, auto-reset HOSE LENGTH: Inlet: 4 feet (1.22 m); drain: 4 feet (1.22 m).

INSTALLATION REQUIREMENTS: Hot and cold water connections with water pressure within 30 – 120 p.s.i. (207 – 827 KPa) range; 120°F to 140°F hot water; a drain; a 120-volt, 60 Hz electrical outlet properly grounded and protected by a 15-amp fuse.

WEIGHTS (Crated/Uncrated): 168 lbs.

MAYTAG® WASHERS



MAYTAG® WASHERS

MOTOR: 1/2 HP rated 120-volt 60 Hz reversible thermally protected against overload, auto-reset HOSE LENGTH: Inlet: 4 feet (1.22 m): drain: 4 feet (1.22 m).

INSTALLATION REQUIREMENTS: Hot and cold water connections with water pressure within 30 – 120 p.s.i. (207 – 827 KPa) range; 120°F to 140°F hot water; a drain; a 120-volt, 60 Hz electrical outlet properly grounded and protected by a 15-amp fuse.

WEIGHTS (Crated / Uncrated): 200 lbs.

from every Maytag dealer.

Models

MAV7504E SAV4655F And

Because of continuing product improvement, Maytag reserves the right to change specifications without notice.

Please note: All models listed here may not be available

Exterior

Color Options

> * Dimensions will vary according to adjustment of leveling legs.
> **Includes 3/4" (1.9 cm) for hinge


on back of washer.

White Bisque

All Maytag® appliances are UL-, AGA-, CSA- or CGA-approved. Dimensional specifications are for planning purposes only. For complete details, see installation instructions packed

Gas dryer dimensions are shown. Electric dryer dimensions are identical to the gas models. Electric models do not have the gas manifold connections or the power cord. Terminal block on electric models only.

MAYTAG® STACKED WASHER AND DRYER



MOTOR: 1/2 HP rated, reversible; thermoprotected against overload; automatic reset ELECTRICAL REQUIREMENT: 120-volt. 60 Hz

FUSE REQUIREMENTS: 15-amp.

HOSE LENGTHS: Inlet Hose: 5 feet (1.5 m). Drain Hose: 4 feet (1.2 m).

MAYTAG® SUPER STACK™ DRYER


MOTOR: 1/4 HP rated, 120-volt, 60 Hz, thermoprotected against overload: automatic reset.

AIRFLOW: 180 cubic feet (5.1 cu. m) per minute.

HEATING ELEMENT (LSE Model): Nichrome helix coil ELECTRICAL RATING (LSE Model): 240-volt, AC, 60 Hz, draws approximately 4,600 watts overall.

AUTOMATIC PRESSURE REGULATOR (LSG Model): Self-adjusting valve automatically compensates for variations in gas pressure.

MAYTAG® COMPACT DRYER



MAYTAG® COMPACT DRYER

HEIGHT — IN. (CM): 331/4 (84.5) WIDTH -- IN. (CM): 231/2 (59.7)

DEPTH — IN. (CM): 23³/₄ (60)

DEPTH (WITH DOOR OPEN) — IN. (CM): 40 (101.6)

MOTOR: 1/s HP, 120-volt, 60 Hz.

EXHAUST: Use a minimum of 4" (10.2 cm) diameter rigid aluminum or galvanized-steel duct. Never use plastic, nonmetal o combustible duct.

Capacity — cu. ft. Controls GentleBreeze™ Drying System Dryness Control Moisture Monitor/Sensor Adjustable Degree Of Dryness Temperature Settings Sound Package Time Dry Cycle

Air Fluff Cycle Damp Dry Cycle Extended Tumble/Wrinkle Out Wrinkle Release

Permanent Press/ Wrinkle-Free Cycle Low/Delicate Temperature

End-Of-Cycle Signal

Drum Light

Dryel® Cycle

Dryer Drum

Stacking Kit

Drying Rack

White Bisque

Color Availability:

LP Kit

Reversible Door

Extra-Large Door Opening

Four-Point Suspension System

Electronic Ignition W/Safety

Shut-Off Valve (Gas Only)

High-Capacity Blower

Ultra Care/Extra-Low Temperature

FEATURES

Front-Load

Compact Dryer

MDE2400

3.7

LED

AutoDry

Melodious Chime

Stainless

MAL2424AXX

MDE/G8400

6.0

Rotary

IntelliDry®

Infinite

Quiet Plus

Variable Chime

DuraCushion™

MAL9000AXX

ΜΔΙ 1100ΔΧΧ†

Maytag® Atlantis® Dryers"

MDE/G7400

6.0

Rotary

IntelliDry®

Quiet Pack

On/Off Chime

DuraCushion[†]

MAL9000AXX

ΜΑΙ 1100ΔΧΧ

MDE/G6400 | SDE/G4606

Rotary

IntelliDry®

Variable

Quiet Plus

On/Off Chime

DuraCushion"

LPK1

DR3

6.0

Rotary

Automatic

Quiet Pack

On/Off Signal

DuraCushion™

MAL9000AXX

ΜΔΙ 1100ΔΧΧ

Maytag® Dryers

SDE/G3606

7.1

Rotary

Automatic

Quiet Plus

On/Off Signal

DuraCushion™

DR3

SDE/G2606

7.1

Rotary

Automatic

DuraCushion"

LPK1

DR3

LSE/G7806

4.7

Rotary

Automatic

Quiet Pack

DuraCushion™

MAYTAG® SUPER STACK™ WASHER

WATER PRESSURE: 20 - 120 p.s.i. (138 - 827 KPa). REQUIRED HOT WATER TEMPS: 120°F to 140°F.

EXHAUST: 4 in. (10.2 cm) duct permits a max. of 54 ft. (16.5 m) rigid aluminum ductwork. Never use plastic, nonmetal or combustible duct.

FUSE REQUIREMENTS: LSE Model: 30-amp. LSG Model: 15-amp.

SINGLE-PORT BURNER (LSG Model): Electric ignition; automatic shut-off.

GAS RATING (LSG Model): 18,000 BTU/hr. for the


LEVELING LEGS: Adjustable, to level unit for proper installation.

WEIGHTS (Entire Unit Crated/Uncrated): 370 lbs. (167.8 kg)/340 lbs. (154.2 kg).


MAYTAG® ATLANTIS® DRYERS

[†]Drying rack with side storage included.

Dryel® is a registered trademark of Procter & Gamble.



MAYTAG® DRYERS



MAYTAG® ATLANTIS® DRYERS

EXHAUST: Use a minimum of 4" (10.2 cm) diameter rigid aluminum or galvanized-steel duct. Never use plastic, noni combustible duct.

HEAT SOURCE/ELECTRICAL REQUIREMENTS: c model - 5,300-watt nichrome helix coil; 240-volt, AC,

Gas model — Single-port burner with automatic electric ignition; 22,000 BTU/hr., 15-amp fuse. Self-adjusting valve automatically compensates for

WEIGHTS (Crated/Uncrated): 145 lbs. (66 kg)/130 lbs. (59 kg).

* Dimensions will vary according to adjustment of leveling legs.

**Includes 3/4" (1.9 cm) for hinge on back of dryer.

MAYTAG® DRYERS

 $\textbf{MOTOR:}~ \ensuremath{\mathcal{V}_{\!\! B}}$ HP, 120-volt, 60 Hz, single-phase, thermally protected against overload, auto-reset.

EXHAUST: Use a minimum of 4" (10.2 cm) diameter rigid aluminum or galvanized-steel duct. Never use plastic, nonmetal or combustible duct.

HEAT SOURCE/ELECTRICAL REQUIREMENTS: Electric model — 5,300-watt nichrome helix coil; 240-volt, AC, 60 Hz;

Solution (22,000 BTU/hr., 15-amp fuse. Self-adjusting valve automatically compensates for variations in gas pressure.

WEIGHTS (Crated/Uncrated): 145 lbs. (66 kg)/130 lbs. (59 kg).

22

23